



## ERASER@Guard

~High Quality Paint Remover~

Product Index : 031

**SANcora®** ERASER@Guard High Quality Paint Remover is an all purpose paint and varnish remover. It is made from a blend of extremely active ingredients which is neither acidic or caustic and can be cleaned by water. It has high penetrating and quick acting properties in the removal of paint and varnish. It is very effective in stripping decorative paint, industrial enamel and most types of coatings. It is non-flammable at room temperature.

<b>Usage</b>	Recommended used for stripping decorative paint, industrial enamel, varnish and most type of coatings.	
<b>Pack Size</b>	0.5 litre, 1 litre and 3 litres.	
<b>Composition</b>	Chemical Content	: Chlorinated Hydrocarbon & Thickening Agent
	Vehicle/Solvent	: Aliphatic & Aromatic Hydrocarbon
<b>Technical Data</b>	Colour	: Milky Opaque
	Specific Gravity	: 1.15 - 1.19
	Viscosity	: 50 - 60 KU/27°C
	Thinner/Cleaner	: Water
<b>Application</b>	Brush/Roller	: Apply with brush or roller generously and leave for 3 - 10 minutes. The applied area is then ready for removal with scraper or other scrapping apparatus. After removing the paint film, clean area with plenty of water. Ensure surfaces to be repainted are free from all traces of <b>SANcora®</b> ERASER@Guard High Quality Paint Remover, dirt, grease or wax.
<b>Surface Preparation</b>	The surfaces of the paint film to be removed preferably should be wire-brushed to improve penetration	
<b>Shelf Life</b>	2 years at ambient temperature in unopened containers.	

### Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.

In case of contact with eye, rinse with plenty of water immediately and seek medical advice.

Remove splashes of paint from skin by using soap or water.

Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.

Ensure good ventilation during application and drying.

Paint must always be stored in upright position and a cool place.

Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.

Refer to Material Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

**SYARIKAT SANLAND PAINT INDUSTRIES SDN BHD (19733-T)**

Plot 52 & 53, Lorong Kilang 15, Tupai Light Industrial Area, 34000 Taiping, Perak Darul Ridzuan, Malaysia.

Tel : 605-8068777 Fax : 605-8074955