



STONE@Guard

~Acrylic Interior & Exterior Stone Dressing~

Product Index : 032

SANcora® STONE@Guard is formulated with acrylic resin. It gives high gloss retention, excellent brushability and abrasion resistance. It is also excellent in acid and alkali resistance and provides a coat of high sheen smooth finish. Suitable for structures with dull and matt cobblestone or tiles surfaces.

Usage	Recommended used for cobblestone pave way or car porch. It is also suitable on matt tiles surface structures.	
Pack Size	1 litre, 5 litres and 18 litres.	
Composition	Binder	: Acrylic Resin
	Vehicle/Solvent	: Aromatic Hydrocarbon
Technical Data	Texture	: High Sheen Smooth Finish
	Theoretical Coverage	: Approx. 15- 17m ² / litre (Depending on surface evenness)
	Drying Time	: Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 3 Hours
		: Hard Dry ≤ 8 Hours
	Recoating Time	: 6 hours
	Thinner/Cleaner	: Mineral Spirit
Application	Brush/Roller	: Ready for use
	Conventional Air Spray	: Ready for use.
	Airless Spray	: Ready for use.
Surface Preparation	Cobblestone or tiles	: Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, sands, grease or wax.
Shelf Life	2 years at ambient temperature in unopened containers.	

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.

In case of contact with eye, rinse with plenty of water immediately and seek medical advice.

Remove splashes of paint from skin by using soap or water.

Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.

Ensure good ventilation during application and drying.

Paint must always be stored in upright position and a cool place.

Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.

Refer to Material Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SYARIKAT SANLAND PAINT INDUSTRIES SDN BHD (19733-T)

Plot 52 & 53, Lorong Kilang 15, Tupai Light Industrial Area, 34000 Taiping, Perak Darul Ridzuan, Malaysia.

Tel : 605-8068777 Fax : 605-8074955