



TRAFFIC@Guard

~Fast Drying Road Marking Paint~

Product Index : 030

SANcora® TRAFFIC@Guard Fast Drying Road Marking Paint is an alkyd modified solvent based paint for road marking i.e. centerlines and edge line of a road, car parking lines and etc. It is fast drying with excellent abrasion resistance and has self-cleaning properties and excellent resistance against bleeding through bitumen.

Usage	For marking of road centerlines, edge lines, car park, pedestrian crossing and etc.	
Pack Size	5 litres	
Composition	Pigment	: Organic & Inorganic
	Binder	: Modified Polyurethane
	Vehicle/Solvent	: Aliphatic & Aromatic Hydrocarbon
Technical Data	Texture	: Low Sheen Smooth Finish
	Theoretical Coverage	: Approx. 8- 10m ² / litre (Depending on surface evenness)
	Drying Time	Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 20 minutes
		: Hard Dry ≤ 60 minutes
	Recoating Time	: 1 hours
	Thinner/Cleaner	: Thinner
Application	Brush/Roller	For normal use, thinning is not necessary. If required, add up to 10% by volume with Thinner.
	Conventional Air Spray	Not Recommended
	Airless Spray	Not Recommended
Surface Preparation	New Surfaces	: Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax.
	Previously Painted Surfaces	: Remove all loose, defective and unstable paint film or powdery residue by brushing and scrapping.
Shelf Life	2 years at ambient temperature in unopened containers.	

Paint Guide

Surface Condition	Finishing - To Paint Two Coats
New Surfaces	SANcora® TRAFFIC@Guard Fast Drying Road Marking Paint
Previously Painted Surfaces	SANcora® TRAFFIC@Guard Fast Drying Road Marking Paint

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Material Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SYARIKAT SANLAND PAINT INDUSTRIES SDN BHD (19733-T)

Plot 52 & 53, Lorong Kilang 15, Tupai Light Industrial Area, 34000 Taiping, Perak Darul Ridzuan, Malaysia.

Tel : 605-8068777 Fax : 605-8074955