



WEATHER@Guard Extra

~ 100% Acrylic Exterior Wall Finish ~

Product Index : 003

SANcora[®] WEATHER@Guard Extra is a premium quality, 100% full acrylic-based emulsion paint. It is specially formulated for tropical climates with excellent weathering properties. It is also fungus and algae resistant. **SANcora**[®] WEATHER@Guard Extra 100% acrylic-based exterior wall finish has excellent alkali resistance, adhesion and durability. It is formulated to provide at least 6 years protection against fungus and algae growth with correct application.

Usage	For decorative and protection of previously-painted or new exterior walls for a long-lasting aesthetic finish.	
Pack Size	1 litre, 5 litres and 18 litres.	
Composition	Pigment	: Organic & Inorganic
	Binder	: Acrylic Polymer Emulsion
	Vehicle	: Water
Technical Data	Texture	: Smooth Matt Finish
	Colour	: A wide range of colours. Please refer to SANcora [®] WEATHER@Guard Extra colour card (Special colour available upon request but subject to minimum batch size)
	Theoretical Coverage	: Approx. 13 - 15m ² / litre (Depending on surface evenness)
	Drying Time	: Single coat at standard thickness (28°C, 50% RH)
		: Touch Dry ≤ 45 minutes
		: Hard Dry ≤ 2 hours
	Recoating Time	: 2 hours
	Thinner/Cleaner	: Water
Application	Brush/Roller	: For normal use, thinning is not necessary. To assist application, can be thinned up to 5% by volume with water.
	Conventional Air Spray	: Thin 5 - 15% by volume with water and adjust to requirement.
	Airless Spray	: Thinning is not required. To assist application, can be thinned 5 - 15% by volume with water.
Surface Preparation	General / New	: Surfaces must be sound, clean, dry and free from all defective or poorly adhering materials, dirt, grease or wax. To have better finish, rub down surface using suitable abrasive and dust off. For the best result, seal with one coat of appropriate SANcora [®] BLOCK@Guard (refer to Paint Guide).
	Previously Painted	: Remove all loose, defective and unstable paint film or powdery residue by brushing thoroughly and scraping. Repair minor defects and cracks with suitable filler.
Shelf Life	2 years at ambient temperature in unopened containers.	

Paint Guide

Surface Condition	Primer - To Paint One Coat	Finishing - To Paint Two Coats
Powdery Surfaces / Alkaline / New Surfaces	SANcora [®] BLOCK@Guard Hi-Performance Wall Sealer	SANcora [®] WEATHER@Guard Extra
Sound Surfaces / Previously Painted Surfaces	SANcora [®] BLOCK@Guard Alkali Resistant Wall Sealer	SANcora [®] WEATHER@Guard Extra

Safety, Health and Environmental Information

When applying paint, it is advisable to wear eye protection and suitable gloves.
 In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
 Remove splashes of paint from skin by using soap or water.
 Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
 Ensure good ventilation during application and drying.
 Paint must always be stored in upright position and a cool place.
 Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
 Refer to Material Safety Data Sheet for complete product safety information.

The above information is given to the best of our knowledge based on our existing laboratory test and practical experience, however since conditions of actual use are beyond our control any recommendations and suggestions are made without warranty, express or implied and we reserve the right to alter the given data without prior notice.

SYARIKAT SANLAND PAINT INDUSTRIES SDN BHD (19733-T)

Plot 52 & 53, Lorong Kilang 15, Tupai Light Industrial Area, 34000 Taiping, Perak Darul Ridzuan, Malaysia.

Tel : 605-8068777 Fax : 605-8074955