



SAN Cora[®]
PAINT

GLOSS@Guard

Matt-Gloss Paint

- Matt Finish
- Fungus Resistant
- Dirt Resistant
- Excellent Coverage & Adhesion
- All Weather Application
- Lead & Mercury Free



SIRIM
CERTIFIED TO MS 125:1995
Certification No.: P9076493




Golden Owl Award
2002, 2004 & 2007
Malaysia 100 Outstanding SMEs

GLOSS@Guard




Matt-Gloss Paint


Product Standard : S/MG/1000 Series



Sundae **GG 1138**



Barley White **GG 1208**



Apple White **GG 1254**




Vogue **GG 1052**




Citrus ****GG 1268**



Ivory **GG 1032**



Papyrus **GG 1056**



Genie **GG 1061**




Royal Yellow ****GG 1228**



Broadcloth **GG 1100**



Cream **GG 1057**



Lavender Posy **GG 1120**



Lemon Yellow ****GG 1328**



Nutmeg **GG 1461**



Maple Cream **GG 1366**




Balmoral Pink **GG 1287**




Orange ****GG 1127**



Golden Honey **GG 1727**



Fire Princess ****GG 1710**



Purple Wave **GG 1504**




Mocha Latte **GG 1686**




Golden Brown **GG 1322**



e. orange **GG 1003**



e. pink ****GG 1002**



Mahogany **GG 1116**




Rustic ****GG 1038**




• Signal Red ****GG 1402**




Scarlet ****GG 1361**



Bronze **GG 1324**



Heritage **GG 1360**



Leather **GG 1037**



Purple Comet **GG 1233**

New

▲ Obsolete colour, available while stock last.


**** Premium Colours**

• Ready Product


Also available in White GG 1102 & Black GG 1103

 Matt Finish
 Fungus Resistant
 Dirt Resistant


 Excellent Coverage & Adhesion
 All Weather Application
 Lead & Mercury Free




Rose White **GG 1176**




Lily White **GG 1207**



Pearl White **GG 1301**




Off White **GG 1300**



Crushed Rock **GG 1015**




Graystone **GG 1012**




Arrow Wood **GG 1928**




Mansard Stone **GG 1029**



Lavender White **GG 1214**



Pewter **GG 1177**




Venus **GG 1406**




Lavender Grey **GG 1695**



Executive Grey **GG 1104**



Dark Grey **GG 1139**



Clear Sky **GG 1805**



Arctic Blue **GG 1445**



Neptune **GG 1031**




Liberty Blue **GG 1281**



Regal Blue **GG 1613**



Wira Blue **GG 1227**




Haze Blue **GG 1305**



Botany Blue **GG 1347**



Mirage **GG 1060**



e. green ****GG 1001**



Pangkor ****GG 1413**



Irish **GG 1605**



Conifer ****GG 1339**



Spruce **GG 1426**

GLOSS@Guard

Matt-Gloss Paint
Product Standard : S/MG/1000 Series



DESCRIPTION

SANCora® Matt GLOSS@Guard is a premium solvent-based with matt finishing, suitable for use on all types of wood and metal surfaces. It is a fungus-resistant matt architectural paint that is easy to apply and forms a smooth tough paint film with excellent durability.

USAGE	For decorative and protection of all types of interior and exterior wood and metal surfaces.		
TECHNICAL DATA	Texture	: Matt Finish	
	Theoretical Coverage	: Approx. 14-16m ² / litre (Depending on surface evenness)	
	Drying Time	: Single coat at standard thickness (28°C, 50% RH)	
		Touch Dry	≤ 1 hours
		Hard Dry	≤ 5 hours
	Recoating Time	: 5 hours	
	Thinner / Cleaner	: White Spirit or Mineral Turpentine	
SURFACE PREPARATION	Wood	: Wood must be dry and free from grease, dirt and other contaminants. Smoothen the surfaces with suitable grade sandpaper and dust off before application of paints.	
	Metal	: Surfaces must be dry and free from grease, dirt and other contaminants. Steel surfaces should be sanded or wire-brushed to remove mill scales and rust. For the best result, steel surfaces should be prepared by hand-powered tool according to BS7079 Part 1:1989 ST3 Standard.	
SHELF LIFE	2 years at ambient temperature in unopened containers.		

PAINT GUIDE

Surface Condition	Primer - To Paint 1 Coat	Undercoat - To Paint 1 Coat	Finishing - To Paint 2 Coats
Wood Surfaces	SANCora® SILVER@Guard	SANCora® UNDERCOAT@Guard	SANCora® Matt GLOSS@Guard
Metal Surfaces	SANCora® RUST@Guard	SANCora® UNDERCOAT@Guard	SANCora® Matt GLOSS@Guard

SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION

When applying paint, it is advisable to wear eye protection and suitable gloves.
In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
Remove splashes of paint from skin by using soap or water.
Keep container tightly closed and away from food, drinks, animal feed and out of the reach of children.
Ensure good ventilation during application and drying.
Paint must always be stored in upright position and a cool place.
Dispose off any paint waste in accordance with the appropriate Environmental Quality Regulations.
Refer to Safety Data Sheet for complete product safety information.

DESKRIPSI

SANCora® Matt GLOSS@Guard adalah cat premium matt berasaskan minyak, sesuai untuk digunakan pada permukaan semua jenis kayu dan logam. Ia adalah cat seni bina matt yang mempunyai sifat daya tahan kulat, mudah untuk dicat dan membentuk satu lapisan cat yang kuat dan daya tahan lama.

PENGUNAAN	Untuk perhiasan dan perlindungan bagi permukaan dalaman dan luaran semua jenis kayu dan logam. Ia juga sesuai digunakan sebagai enamel marin untuk bahagian atas, dek kapal dan bilik-bilik enjin.		
DATA TEKNIKAL	Tekstur	: Kemasan Licin Kilauan Tinggi	
	Liputan Teori	: Anggaran. 14 - 16m ² / liter (Bergantung pada kelicinan permukaan)	
	Tempoh Kering	: Satu lapisan dengan ketebalan standard (28°C, 50% RH)	
		Kering Disentuh	≤ 1 hours
		Kering Sempurna	≤ 5 hours
	Tempoh Lapisan Semula	: 5 jam	
	Pencair / Pencuci	: Spirit Putih atau Turpetin Mineral	
PENYEDIAAN PERMUKAAN	Kayu	: Kayu perlulah kering dan bebas daripada minyak, kekotoran, dan sebarang pencemaran. Licinkan permukaan dengan gred kertas pasir yang sesuai dan bersihkan habuk sebelum mula mengecat.	
	Logam	: Permukaan perlu kering dan bebas daripada minyak, kekotoran dan sebarang pencemaran. Permukaan logam perlu dibersihkan menggunakan kertas pasir atau berus dawai untuk mengeluarkan kesan kimia dan karat. Untuk kemasan yang terbaik, permukaan logam perlu disediakan menggunakan alat kuasa tangan berdasarkan BS7079 Part 1:1989 ST3 Standard.	
JANGKA HAYAT	2 tahun pada suhu ambien dalam bekas tertutup.		

PANDUAN MENGECA

Keadaan Permukaan	Primer - Cat 1 Lapisan	Undercoat - Cat 1 Lapisan	Kemasan - Cat 2 lapisan
Permukaan Kayu	SANCora® SILVER@Guard	SANCora® UNDERCOAT@Guard	SANCora® Matt GLOSS@Guard
Permukaan Logam	SANCora® RUST@Guard	SANCora® UNDERCOAT@Guard	SANCora® Matt GLOSS@Guard

INFOMASI KESELAMATAN, KESIHATAN DAN PERSEKITARAN

Semasa mengecat adalah disyorkan memakai perlindungan mata dan sarung tangan yang sesuai.
Jika mata terkena cat, cuci dengan air yang banyak dan segera berjumpa doctor.
Bersihkan sebarang cat yang terkena pada kulit dengan sabun dan air.
Pastikan tong cat ditutup rapat dan jauhkan daripada makanan, minuman dan kanak-kanak.
Pastikan ada ventilasi yang baik semasa pengecatan dan pengeringan.
Tong cat mesti disimpan dalam keadaan tegak dan kawasan yang sejuk.
Buangkan semua sisa cat menurut Peraturan Kualiti Alam Sekitar.
Rujuk kepada lembaran SDS untuk maklumat yang lebih terperinci.



Part of **KANSAI PAINT**

Paint Manufacturer
SANCORA PAINTS INDUSTRIES SDN BHD
197401002682 (19733-T)
(Wholly Owned Subsidiary Of Kansai Paint Asia Pacific Sdn Bhd)

Lot 8206, Kawasan Perusahaan Kamunting, 34600 Kamunting, Perak, Malaysia.
Tel +605-891 8777 (8 lines) **Fax** +605-891 2277 **Email** info@sancora.com
Website www.sancora.com **Facebook** www.facebook.com/sancorapaint

Quality and Environmental Management System
MS ISO 9001 and 14001

More on **SANCora®**



The information contained herein is subject to change as may be required by the company without any further notice.

Rev : 06